• .		-	¥	UTA	AH OIL AND (	GAS CONSERVAT	TION CO	OMMISSION	+	1
REMARKS: WELL LO		ELECTRIC I	ogs	frLE	X wati	ER SANDS	_LOCATI	ON INSPECTED GAS WE	LL SUB. REPORT/	abd.
* Locati	on	Abandor	red -	weu	revex	2 drille	<u>d -</u>	4-8-82-0	per-Regi.	
									0	
		.=								
							40			
DATE FILED	5-2	21-81								
LAND: FEE & PATENTED		STATE LEASE N	IO.			PUBLIC LEA	ASE NO.	U-013793-A	INDIAN	
DRILLING APPROVED:	7-9	-81								
SPUDDED IN:										
COMPLETED:			PUT TO PRO	DUCING:						
INITIAL PRODUCTION:					-					
GRAVITY A.P.I.										
GOR:								-		
PRODUCING ZONES:										
TOTAL DEPTH:					···.					
WELL ELEVATION:		***								· · · · · · · · · · · · · · · · · · ·
DATE ABANDONED:	A	10-19-	82	~~						
FIELD:	UNE	ESICNATE	3/8	76 21	etund	Buttes				
UNIT:	RIV	ER BEND								
	TITA	TETT A T.T								

COUNTY: UINTAH

RIVER BEND UNIT 4-23F

FT. FROM (N) (M LINE,

OPERATOR

236'

NW NW

**OPERATOR** 

SEC.

1/4 - 1/4 SEC.

API NO. 43-047-31015

23

WELL NO.

LOCATION

TWP.

RGE.

20E

660'

SEC.

23

10\$

MAPCO PRODUCTION CO.

TWP

FT. FROM (K) (W) LINE.

RGE.

# UNITED STATES DEPARTMENT OF THE INTERIOR

SUBMIT IN CLICATE\*

(Other instruments on reverse side)

Form approved. Budget Bureau No. 42-R1425.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK  1a. TTEP OF YORK  1b. WIFE OF WELL    D. WIFE OF WELL   OR   OF PERMIT TO DRILL   DEEPEN, OR PLUG BACK   D. WIFE OF WELL   OR   OF PERMIT TO DRILL   DEEPEN, OR PLUG BACK   D. WIFE OF WELL   OR   OF PERMIT   OR PERMIT   OR PLUG BACK   WALK   OF PERMIT   OR PERMIT   OR PLUG BACK   WALK   OF PERMIT   OR PERMIT   OR PLUG BACK   WALK   OR PLUG		DEPARTMEN	I OF THE I	NIEF	RIOR		5. LEASE DESIGNATION AND SERIAL NO.	
In TYPE OF WORK    DRILL IX   DEEPEN   PLUG BACK   River Bend		U-013793-A	4					
DRILL [X] DEEPEN DEEPEN DIVISION SAME STORE STORE River Bend River		6. IF INDIAN, ALLOTTEE	OR TRIBE NAME					
RIVER Bend  OILL OAR DO OTHER DOOR DOOR DOOR DETERM DOOR DOOR DOOR DOOR DOOR DOOR DOOR DO		ILL [X]	DEEPEN		PLUG BAC	ж 🗀	7. UNIT AGREEMENT NAME	
**State of Unitarian No.**  **Pressure of Unitarian No.**  **MAPCO Production Company**  **State Ordination Company**  **At surface NM NW (660)** Et & 236 * FWL) Sec. † † † † † 105, R20E  **At proposed prod. 2005**  **State Ordination Company**  **At proposed prod. 2005**  **At prod.	b. TYPE OF WELL					-	River Bend	*:
MAPCO Production Company  8. ANDRESS OF OVERLANDE 10. SEED AND FOOL, OR WILDOW 10. GEVEL NO. 10. SEED AND FOOL, OR WILDOW 10. SEED AND FOOL, OR WILDOW 11. SEED AND FOOL, OR WILDOW 11. SEED AND FOOL, OR WILDOW 12. SEED AND FOOL, OR WILDOW 11. SEED AND FOOL, OR WILDOW 12. SEED AND FOOL, OR WILDOW 13. SEED AND FOOL, OR WILDOW 13. SEED AND FOOL, OR WILDOW 14. DISTANCE IN MILES AND PRESCRIPT OR FAIL 15. SEED AND FOOL, OR WILDOW 15. SEED AND FOOL, OR WILDOW 16. SEED AND FOOL, OR WILDOW 17. SEED AND FOOL, OR WILDOW 18. SEED AND FOOL, OR WI	well w	AS OTHER				ræ 🗌	8. FARM OR LEASE NAM	CIG.
10. PRILE OF PROLE SIZE OF CASING AND CASING AND CENTENTING PROPOSED CASING AND CENTENTING PROPERTY OF CHARGE TO 1.2—1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pip. 1. Fest and logs. Release drilling rig. Casing program may be modified to provide added burst strength in needed for frac program.  3. Release and proposed the surface are proposed. Size of the proposed provide and proposed provide program. The proposed is to despen directionally, preverse program. The proposed provide proposed proposed proposed		ian Campani						
4. DOCATION OF WILLIAMS AVE. SUITE 202, Billings, MT 59102  4. DOCATION OF WILLIAMS CHEEK CHEEK CHEEK THAT IN EXCELLING CHEEK THAT IN EXCELLING CHEEK THAT IN EXCELLING CHEEK THAT IN EXCELLING CHEEK THAT IN CHEEK		Ton Company					<u>.</u>   ·	
4 ENCATION OF WELLY, REPORT DECAIDS CORTED AT BOTT OF THE ANY STATE PROPERTY OF THE AND SHAPE AND SHAP		a Suita 202	Dillings	MT EO	100			
At proposed prod. zone  Same  14. DISTANCE IN MILES AND DIRECTION FROM NEARIST TOWN OR POST OFFICE*  15. IN MILES SOUTH OF OUTSELL 23  16. NO. OF ACERS IN LEASE LINE. THE SOUTH OF OUTSELL 23 IN THE LOCATION OF DEALER PROPERTY OF ALERS LINE. THE LOCATION OF DEALER PROPERTY DEALER WORK WILL START OF THE LOCATION OF ALERS WILL START OF THE LOCATION OF ALERS WORK WILL START OF THE LOCATION OF ALERS WORK WILL START OF THE LOCATION OF THE LABLAS LINE. THE LOCATION OF	4. LOCATION OF WELL (R	enort location clearly ar	d in accordance wi	th any S	tate requirements *)		10. FIELD AND POOL, O	B WILDCAT
Sec. +6, T105, R20E	At surface NW NW	(660' <b>FSL</b> & 23	6' FWL) Sec	. <del>10</del> ,	T10S, R20E	*	AND SURVEY OR AR	EA.
12. COUNT OF PARKET   12. STATE   12. COUNT OF PARKET   12. COUNT OF PARKET   13. STATE   14. In that   14. In that   14. In that   14. In that   15. In t	At proposed prod. zon	<sup>le</sup> Same						DODE
### DITTED SOUTH OF Oursay    Link	14. DISTANCE IN MILES	AND DIRECTION FROM NE	AREST TOWN OR POS	ST OFFICE	p.*			
16. No. OF ACERS IN LEASE   17. No. OF ACERS ASSIGNED TO THE MALL   17. NO. OF ACERS ASSIGNED TO THIS WALL   17. NO. OF ACES ASSIGNED TO THIS WALL   17. NO. OF ACES ASSIGNED TO THIS WALL   17. NO. OF ACES ASSIGNED TO THIS WALL   17. NO. OF	± ]] miles so	uth of Ourav						ļ.
PROPOSED LEASE LINE, FT.  (Also to nearest drig, unit line, it any)  18. Descriptions provided Locations and the state of	15. DISTANCE FROM PROPO	OSED*		16. NO	. OF ACRES IN LEASE		OF ACRES ASSIGNED	<del></del>
18. DISTANCE FROM PROPOSED LOCATION TO MEMBER WILL DILLING, COMPLETED, 5800' ±6185 LLDGGGG ROTARY OF CABLE TOOLS TO MEMBER WILL DILLING, COMPLETED, 5800' ±6185 LLDGGGG ROTARY OF CABLE TOOLS ROTARY OF CABLE TOOLS ROTARY OF CABLE TOOLS ROTARY OF CABLE TOOLS TOOLS AND THE WORK WILL START' 4987' GL  SIZE OF ROLE SIZE OF CASINO WEIGHT PER POOT SETTING DEPTH QUANTITY OF CEMENT 7/15/81  SIZE OF ROLE SIZE OF CASINO WEIGHT PER POOT SETTING DEPTH QUANTITY OF CEMENT 12-1/4" 8-5/8" 24# 400' Cmt to surface 7-7/8" 4-1/2" 11.6# ±6185' Cmt to surface 1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pip 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ANDVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or pluz back, give data on present productive sone and proposed new productive sone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout proventer program. If any.  APPROVED BY Engr. Tech.  PATE 5-19-81  (This space for Federal or State office use)	PROPERTY OR LEASE I	INE, FT.	2361	1	600	TOT		Tariha kul Antigora
ON APPENDED BY. DATE PROPOSED PROCESSING AND CEMENTING PROGRAM  22. APPROX. DATE WORK WILL STARF* 4987 GL  PROPOSED CASING AND CEMENTING PROGRAM  SIZE OF ROLE  SIZE OF CASING  PROPOSED CASING AND CEMENTING PROGRAM  SIZE OF CASING  12-1/4" 8-5/8" 24# 400' Cmt to surface  7-7/8" 4-1/2" 11.6# ±6185' Cmt to surface  1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and ceme to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pip. 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE BFACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone and measured and true vertical depths. Give blowou reverteet program. If any.  BERNIE NO.  APPROVAL DATE	18. DISTANCE FROM PROP	OSED LOCATION*				20. ROTA		eg est variable en
22. APPROX. DATE WORK WILL STARTY  4987' GL  PROPOSED CASING AND CEMENTING PROGRAM  SIZE OF ROLE  12-1/4" 8-5/8" 24# 400' Cmt to Surface  7-7/8" 4-1/2" 11.6# ±6185' Cmt to surface  1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cement to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pipers and the surface of the s		RILLING, COMPLETED, IS LEASE, FT. 5	800'	±6	185 Istaland	Rot	arv	er andre Monthalt
PROPOSED CASING AND CEMENTING PROGRAM    SIZE OF ROLE   SIZE OF CASING   WEIGHT PER POOT   SETTING DEPTH   QUANTITY OF CEMENT	21. ELEVATIONS (Show who				KIHLL			
SIZE OF HOLE  SIZE OF ROLE  12-1/4"  8-5/8"  24#  400'  Cmt to surface  7-7/8"  1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cement to surface.  1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cement to surface.  2. NU and pressure test BOP stack (see Fig. I) prior to drilling out below surface pipe 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive sone and proposed new productive program, if any.  APPROVED BY.  APPROVED BY.  TITLE  Engr. Tech.  DATE 5-19-81	4987' GL				But		7/15/81	
12-1/4" 8-5/8" 24# 400' Cmt to surface 7-7/8" 4-1/2" 11.6# ±6185' Cmt to surface  1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pipe 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.  11 Engr. Tech.  12 DATE 5-19-81  (This space for Federal or State office use)	23.		PROPOSED CASI	NG ANI	CEMENTING PROGRA	M		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface piper as daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE SPACE DESCRIBE PROFOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive sone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowon reverence program, if any.  11. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface pipe.  12. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pipe.  13. Drill a 12-1/4" hole with a salt water mud system. No cores are planned.  14. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned.  15. Run of the specific pipe.  16. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  16. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  17. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, give pertinent data on subsurface locations and measured and true vertical depths. Give blowon proventer program, if any.  18. Drill a 7-7/8" hole to ±6185' with a salt water mud system				гоот			QUANTITY OF CEMEN	T .
1. Drill a 12-1/4" hole with an air rig to 400'. Run 8-5/8", 24# K-55 casing and cemer to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pipe 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive sone and proposed new productive sone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program. If any.  816NED Primary Daman Title Engr. Tech.  917 DATE 5-19-81  (This space for Federal or State office use)			_					
to surface.  2. NU and pressure test BOP stack (see Fig. 1) prior to drilling out below surface pips 3. Test pipe rams daily and blind rams as possible.  4. Drill a 7-7/8" hole to ±6185' with a salt water mud system. No cores are planned. DST's will be run as needed to evaluate unexpected shows.  5. Run logs. Set 4-1/2", 11.6#, K-55 and N80 casing as dictated by drilling shows, tests and logs. Release drilling rig. Casing program may be modified to provide added burst strength if needed for frac program.  6. Primary zones of interest are the Upper Wasatch and Chapita Wells sections of the Wasatch.  7. RU completion rig to test in a normal, prudent manner, all zones that indicate a potential for economically, recoverable reserves.  (See back for log tops)  IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.  24.  SIGNED PLANA Bauman TITLE Engr. Tech.  DATE 5-19-81  (This space for Federal or State office use)	/ <del>-</del> 7/8"_	4-1/2"	11.6	#	±6185'		Cmt to surfa	ce T
SIGNED PERMIT NO	3. Test pipe 4. Drill a 7    DST's wil 5. Run logs.    tests and added bur 6. Primary z    Wasatch. 7. RU comple potential (See back for	rams daily an -7/8" hole to 1 be run as ne Set 4-1/2", logs. Releas st strength if ones of interetion rig to te for economicallog tops)	d blind ram ±6185' with eded to eva ll.6#, K-55 e drilling needed for st are the st in a nor lly, recove	s as a sa luate and rig. frac Upper mal, rable	possible. It water mud sy unexpected sho N80 casing as o Casing program program. Wasatch and Chprudent manner, reserves.	vstem. Dws. lictate nay b napita all z	No cores are ed by drilling be modified to Wells sections zones that indi	planned. shows, provide of the cate a
(This space for Federal or State office use)  PERMIT NO APPROVAL DATE APPROVED BY THE STATE OF UTAM DIVISION OF		1 10			Engn Toch	· · · · · · · · · · · · · · · · · · ·	£ 10	01
APPROVED BY TITLE CP UT AND DIVISION CP	(This space for Fede		TI	TLE	Engl. (Coll.		DATE	
APPROVED BY TITLE CF UT AND DIVISION OF					,	٠		
	PERMIT NO.				APPROVAL DATE	PPR	DVED BY THE	ESTATE
	I Danoven ***						MAN DIVID	
		AL, IF ANY:	TI	TLE				**

#### nstructions

General: This form is designed for submitting proposals to perform certain well operations, as indicated, on all types of lands and leases for appropriate action by either a Federal or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable State or Federal regulations concerning subsequent work proposals or reports on the well.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on this reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal or State agency offices.

Items 15 and 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective production zone.

Item 22: Consult applicable Federal-or State regulations, or appropriate officials, concerning approval of the proposal before operations are started.

#### LOG TOPS:

Green River	1119
Wasatch Tongue	י9899
Wasatch	43761
Chapita Wells	5016'
Uteland Buttes	6084



# MAPCO, INC. WELL LOCATION PLAT

LOCAT IN THE NWY OF THE NWY OF SECTION 10, T10S, R20E, S.L.B.&M.

MAY 1 5 1981

,	R. B.	U. 2	4 - 23 F 80.02 Chs	•		WAY 15 to
23 Chs	236	R. B. U.	4-23F ELEV. 4987'			1
80.2					<del> </del>	
N 00 13' W						NORTH
				23 —		
						SCALE: 1"=1000'
						Exhibit A
i			:			

# LEGEND & NOTES

◆ FOUND ORIGINAL CORNER USED FOR THIS SURVEY. :

I hereby certify that this plat was prepared from field notes of an actual survey performed by me, during which the shown monuments were found or established.

SURVEYOR'S CERTIFICATE

GENERAL LAND OFFICE PLAT WAS USED FOR REFERENCE AND CALCULATIONS. THE BASIS OF BEARINGS WAS DETERMINED BY SOLAR OBSERVATION.

Jerry D. Allred, Registered Land Surveyor, Cert. No. 3817 (Utah)

JERRY D. ALLRED & ASSOCIATES Surveying & Engineering Consultants

> 121 North Center Street P.O. Drawer C **DUCHESNE, UTAH 84021** (801) 738-5352

# TEN-POINT COMPLIANCE PROGRAM OF NTL-6 APPROVAL OF OPERATIONS

Utah

Attached to Form 9-3310 /

Company: MAPCO PRODUCTION COMPANY

Well: RBU 4-23F

Well Location: 660' FSL and 236' FWL

Section 10, 710S, R20E

County: Uintah State:

# 1. Geologic Surface Formation

UINTAH

#### 2. Estimated Important Geologic Markers

Formation	Depth
Vintah	Surface
Green River	1119
Wasatch	4376
Chapita Wells	5016
Uteland Buttes	6084

# 3. Estimated Depths of Anticipated Water, Oil, Gas or Minerals

Formation	Depth	Remarks
Wasatch Tongue	3899	gas
Wasatch	4376	gas
Chapita Wells	5016	gas
Uteland Buttes	6084	gas

# 4. The Proposed Casing Program

SIZE OF CASING	WEIGHT & GRADE	SETTING DEPTH	QUANTITY OF CEMENT
8-5/8" 4-1/2"	24# K-55 11.6# K-55 & N-80	400 ' ±6185 '	Cmt to surface Cmt to surface

TEN-POINT COMPLIANCE PROGRAM OF NTL-6

Well: RBU 4-23F

Page 2

# The Operator's Minimum Specifications for Pressure Control

See Figure #1, attached. BOP stack has a 3000 psi working pressure. BOP's will be pressure tested before drilling casing cement plugs. Pipe rams will be operated daily and blind rams as possible.

# The Type and Characteristics of the Proposed Circulating Muds

The well is to be drilled with a saltwater mud system maintaining a weight of approximately 9#/gal with weighting material on location sufficient to weight-up for pressure control.

# The Auxiliary Equipment to be Used

1.) Kelly cock.

Full opening valve on floor with DP connection for use when Kelly is 2.) not in string.

Pit volume totalizer equipment will be used.

# The Testing, Logging, and Coring Programs to be Followed

A two (2) man mud logging unit will be in operation from surface to T.D. The following open hole logs will be run:

1.) GR-DLL

2.) FDC-CNL-Caliper


Exact logging detail and procedures will be prepared prior, to reaching

# Any Anticipated Abnormal Pressures or Temperatures Expected


No abnormal pressures are anticipated nor is the area known for abnormal temperatures. The formations to be penetrated do not contain  $\mathrm{H}_2\mathrm{S}$  gas.

10.	The Anticipated	Starting Da:	te and Duration of the Operations	
	Starting Date:		The operations	
	Duration:	15 days		

# BOP STACK



# CHOKE MANIFOLD



## MULTI-POINT REQUIREMENTS TO ACCOMPANY APD

Attached to Form 9-331C

COMPANY: MAPCO PRODUCTION COMPANY

WELL: RBU 4-23F

WELL LOCATION: 660'-FSL and 236' FWL

Section 10, T10S, R20E

County: Uintah State: Utah

#### Existing Roads

A. The proposed well site and elevation plat is shown as Exhibit A.

- В. Location is as shown in Exhibit B.
- C. An access road of about  $\pm$  2200' will be needed to reach the location from the existing road as shown in Exhibit B.
- D. All existing roads are shown on Exhibits B & D.
- There is no anticipated construction on any existing roads.

#### 2. Planned Access Roads

- Maximum of 30' right-of-way with road bed being approximately 1. Width: 16'-18', and remainder of right-of-way to be used for borrow ditches.
- 2. Maximum grade:
- 3. Turnouts: None
- 4. Drainage design: Drain ditches along either side of the road, where necessary for drainage with material from borrow ditch used to build crown of road. As per meeting with BLM, BIA & USGS on May 3, 1979. No speed curves

on hills.

- 5. Culverts: None
- Surface materials: Native dirt.
- 7. Gates, cattleguards, fence cuts:

Page 2

MULTI-POINT REQUIREMENTS TO ACCOMPANY APD

Well: RBU 4-23F

# 3. Location of Existing Wells

All existing wells known in the area are shown directly on Exhibit B within the one-mile radius.

1. Water wells:

None

2. Abandoned wells:

None

Temporarily abandoned wells:

None

4. Disposal wells:

None

5. Drilling wells:

None

6. Producing wells:

RBU 7-22F, 11-15F, 8-14F

7. Shut-in wells:

<sup>\*</sup> RBU 15-23F

8. Injection wells:

None

9. Monitoring or observation wells:

# 4. Location of Existing and/or Proposed Facilities

- A. The location of existing and/or proposed facilities, if any, owned or controlled by lessee/operator within the 1-mile radius will be shown on Exhibit B.
- 1. Tank batteries: None
- 2. Production facilities: RBU 7-22F, RBU 11-15F, RBU 8-14F
- Oil gathering lines: None
- 4. Gas gathering lines: See Exhibit B

- 5. Injection Lines: None
- 6. Disposal Lines: None
- B. It is contemplated that, in the event of production, all new facilities will be easily accommodated on the drill pad on the solid base of cut and not placed on the fill areas.
  - 1. No flagging then will be needed.

Page 3
MULTI-POINT REQUIREMENTS TO ACCOMPANY APD
Well: RBU 4-23F

- 2. The dimensions of the production facilities and the location of facilities is drafted on Exhibit C. If production is obtained, then the unused areas will be restored as later described.
- Concrete as needed and any gravels needed will be purchased from private sources.
- 4. All pits will be fenced to minimize any hazard to sheep, cattle, antelope and other animals that graze the area. Flagging material will be used as needed, if water or other fluid is produced.
- C. Rehabilitaion, whether the well is productive or dry, will be accomplished as soon as possible in those areas already described, and in accordance with Item 10 following.

## 5. Water Supply

Water source is shown on Exhibit D.

- A. Water will be hauled by a private hauler from a permitted location.
- B. No pipelines are anticipated. Hauling will be on the road(s) shown in Exhibit D.
- C. No water well is anticipated to be drilled at this time.

# Source of Construction Materials

- A. No construction material, insofar as drilling, will be needed.
- B. No construction materials will be obtained from Federal or Indian land.
- C. The native materials that will be used in the construction of this location site and access road will consist of sandy-clay soils and sandstone and shale materials gathered in actual construction of the road and location.
- D. Access roads crossing federal lands are shown under Items 1 & 2.

# 7. Handling Waste Disposals

- 1. Drill cuttings will be buried in the reserve pit when covered.
- 2. Drilling fluids will be handled in the reserve pit.
- Any produced fluids during drilling tests or while making production tests will be collected in reserve pit.

- 4. Any sewage will be covered or removed and chemical toilets will be provided.
- 5. Garbage and other waste material will be enclosed in a wire mesh container, and then disposed of in an approved waste disposal facility.
- 6. After the rig moves out, all materials will be cleaned up and no adverse materials will be left on location. Any dangerous open pit will be fenced or covered.

## 8. Ancillary Facilities

No proposed airstrip, camp, or other facility will be constructed during the drilling or completion of this well.

## 9. Well Site Layout

- 1. Exhibit E is the drill pad layout on a scale of 1" = 40'.
- 2. & 3. Exhibit E is a layout of the drilling rig, pits, and burn pits. Parking and trailers will be along the <u>sw</u> side of the area as shown. The access road will be from the <u>north</u>. Soil stockpiles are also shown on Exhibit E.
- 4. The reserve pit will not be lined. Steel mud pits may be used, at least in part, during drilling operations.

# 10. Plans for Restoration

- Backfilling, leveling and gentle sloping is planned and will be accomplished as soon as possible after plugging or setting of production casing. Waste disposal and spoils materials will be burried or hauled away immediately after operations cease from drilling and/or completion.
- 2. The soil banked materials will be spread over the area and gentle sloping or contouring to meet the existing terrain. Revegetation will be by planting of native vegetation to the area or some other combination as recommended by The Bureau of Land Management.

The access road to the drill pad will be revegetated, if needed. Any damage to present existing roads will be repaired as needed.

3. Prior to rig release, the pits will be fenced on the fourth side and so maintained until cleanup is accomplished. The reserve pit will have fencing on three sides during drilling.

Page 5
MULTI-POINT REQUIREMENTS TO ACCOMPANY APD
Well: RBU 4-23F

- 4. If any oil is on the pits, and is not immediately removed after operations cease, then the pit will be flagged overhead to keep birds and fowl out.
- 5. The commencement of rehabilitation operations will begin as soon as possible after drilling ceases. Planting will be planned as suggested by BLM.

## 11. Other information

1. <u>Topography</u>: See <u>NOTES</u>, Exhibit E

Soil Characteristics and Geologic features: The soils of this semi-arid area are of the Uinta and Duchesne River formation (The Fluvial Sandstone & Mudstone) from the Eocene Epoch and Quaternary Epoch (gravel surfaces) and the visible geologic structures consists of light brownish-gray clays (OL) to sandy soils (SM-ML) with poorly graded gravels and shales with out crops of rock (sandstone, mudstone, conglomerates and shales).

Flora: Areas of sagebrush, rabbitbrush, some grasses and cacti, and large areas of bare soils devoid of any growth.

Fauna: Is sparse but consists predominantly of the mule deer, coyotes, pronghorn antelope, rabbits, and varieties of small ground squirrels and other types of rodents, and various reptiles common to the area. Birds of the area are raptors, finches, ground sparrows, mag pies, crows and jays.

 Type of surface use activity: Primary purpose is grazing domestic livestock.

Surface ownership of all involved lands: BLM

3. Proximity of usable water (Shown on Exhibit D):

Occupied dwellings (if any, shown on Exhibit B): None

Archaeological or historical sites (if any, shown on Exhibit B): A.E.R.C. of Bountiful, UT will do the archeological study.

Page 6
MULTI-POINT REQUIREMENTS TO ACCOMPANY APD
Well: RBU 4-23F

# 12. Lessee's or Operator's Representative

James D. Holliman
Manager of Operations
MAPCO Production Company
Alpine Executive Center
1643 Lewis Ave., Suite 202
Billings, Montana 59102

Phone: (406) 248-7406

or (406) 656-8435 Darwin Kulland
District Superintendent
MAPCO Production Company
P.O. Box 1360
Roosevelt, Utah 84066

Phone: (801) 722-4521

## 13. Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the condition which presently exists; that the statements made in this plan are, to the best of my knowledge true and correct; and, that the work associated with the operations proposed herein will be performed by MAPCO PRODUCTION COMPANY and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.


or


May 19, 1981


DATE

Manager of Operations


TITLE







# MAPCO, INC. WELL LAYOUT PLAT R.B.U. 4-23F



# \*\* FILE NOTATIONS \*\*

DATE: 5/29/8)	
OPERATOR: Mapor Production	on) Co.
WELL NO: RBU 4-23F	
Location: Sec. # T. 105 R	. 20E County: Gentah
<b>/</b>	Entered on N.I.D:
Card Indexed:	Completion Sheet:
API Number	43-047-31015
CHECKED BY:	
Petroleum Engineer: M.S. Mu	Jude 7/8/8/
Director:	
Administrative Aide: 300 club	to WYW' that badry
	:
APPROVAL LETTER:	
Bond Required:	Survey Plat Required:
Order No.	0.K. Rule C-3
Rule C-3(c), Topographic Exception within a 660' radius o	- company owns or controls acreage of proposed site
Lease Designation Sect	Plotted on Map
Approval Lette	written
Hot Line P.I.	

Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

5. LEASE

# UNITED STATES DEPARTMENT OF THE INTERMEDIN OF

DEPARTMENT OF THE INTERPORT OF	U-013793-A
GEOLOGICAL SURGEY, GAS & MINING	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME River Bend Unit 8. FARM OR LEASE NAME
1. oil	9. WELL NO. RBU 4-23F  10. FIELD OR WILDCAT NAME River Bend  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23, T. 10 S., R. 20 E.  12. COUNTY OR PARISH UT  14. API NO.  15. ELEVATIONS (SHOW DF, KDB, AND WD) 4987 GL  (NOTE: Report results of multiple completion or zone change on Form 9-330.)
Please see revised plat. The only change in description of the legal location. The original and should read Section 23.  Subsurface Safety Valve: Manu. and Type	the plat is the written inal plat said Section 10
18. I hereby certify that the foregoing is true and correct	
SIGNED Richard Baumann HTLE Engr. Tech.	DATE 6-22-81
(This space for Federal or State of	ice use)
APPROVED BY TITLE TITLE	DATE

# MAPCO, IN WELL LOCATION PLAT

LOCATE. THE NWZ OF THE NWZ OF SECTION 23, T10S, R20E, S.L.B.&M.

R. B. U. 4 - 23 F

	1. D. O. 5 88° 33'	W 80.02 Chs		
80.23 Chs	79 9 R. B. U. 236' GROUND	4-23F ELEV. 4987'		
N 00 13' W			23	



SCALE: 1"=1000'

#### LEGEND & NOTES

◆ FOUND ORIGINAL CORNER USED FOR THIS SURVEY.

SURVEYOR'S CERTIFICATE

I hereby certify that this plat was prepared from field notes of an actual survey performed by me, during which the shown monuments were found or established.

GENERAL LAND OFFICE PLAT WAS USED FOR
REFERENCE AND CALCULATIONS. THE BASIS
OF BEARINGS WAS DETERMINED BY SOLAR OBSERVATION.

Jerry D. Allred, Registered Land Surveyor, Cert. No . 3817 (Utah)



JERRY D. ALLRED & ASSOCIATES

Surveying & Engineering Consultants

121 North Center Street P.O. Drawer C DUCHESNE, UTAH 84021 (801) 738-5352 July 9, 1981

Mapco Production Company 1643 Lewis Ave., Ste. #202 Billings, Montana 59102

RE: Well No. River Band Unit #4-23FF Sec. 23, T. 10S, R. 20E, Uintah County, Utah

Insofar as this office is concerned, approval to drill the above referred to gas well is hereby granted in accordance with Section 40-6-11, Utah Code Annotated 1953: and predicated on Rule A-3, General Rules and Regulations and Rules of Practice and Procedure.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to <u>immediately</u> notify the following:

MICHAEL T. MINDER - Petroleum Engineer Office: 533-5771 Home: 876-3001

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-047-31015.

Sincerely,

DIVISION OF OIL, GAS, AND MINING

Bonn &

Michael T. Minder Petroleum Engineer

MTM/db CC: USGS



Scott M. Matheson, Governor Temple A. Reynolds, Executive Director Cleon B. Feight, Division Director

4241 State Office Building • Salt Lake City, UT 84114 • 801-533-5771

April 5, 1982

Mapco Production Company 1643 Lewis, Ste. 202 Billings, Montana 59102

> Re: Well No. RBU #4-23F Sec. 23, T. 10S, R. 20E. Uintah County, Utah

#### Gentlemen:

In reference to the above mentioned wells, considerable time has gone by since approval was obtained from this office.

This office has not received any notification of spudding. If you do not intend to drill these wells, please notify this Division. If spudding or any other activity has taken place, please send necessary forms. If you plan to drill this location at a later date, please notify as such.

Your prompt attention to the above will be greatly appreciated.

Very truly yours,

DIVISION OF OIL, GAS AND MINING

Cari Furse Clerk Typist



# PRODUCTION COMPANY

April 8, 1982

State of Utah Natural Resources & Energy Oil, Gas & Mining 4241 State Office Building Salt Lake City, UT 84114

Attn: Ms. Cari Furse

Re: RBU 4-23F

Sec. 23, T. 10 S., R. 20 E.

Uintah County, Utah

Dear Ms. Furse:

MAPCO Production Company does not intend to drill the above referenced well.

Very truly yours,

MAPCO Production Company

R. E. Baumann

Engineering Technician

REB/ch



DIVISION OF OIL, GAS & MINING

Oil and Gas Operations 2000 Administration Building 1745 West 1700 South Salt Lake City, Utah 84104 October 14, 1982 Mapco Production Company 1643 Lewis Ave. - Suite 202 Billings, Montana 59102 Application for Permit to Drill Re: Well No. 4-23F Section 23-T10S-R20E Uintah County, Utah Lease No. U-013793-A Gentlemen: The referenced Application for Permit to Drill was received in this office on May 22, 1981. Review of the application disclosed that a Right-of-Way was needed from the BIA. This office cannot process the application without the Right-of-Way, and therefore is returning your application unapproved. This office will commence processing the application upon receipt of a new, complete package. If you have any questions, please feel free to call. Sincerely, E. W. Guynn District Oil & Gas Supervisor bcc: SMA BIA State O&G " MMS-Vernal Well File APD Control DH/dh

October 19,1982

Mapco Production Company 1643 Lewis Avenue, Suite 202 Billings, Montana 59102

RE: Well No. 4-23F

Sec. 23, T. 10S, R.20E Uintah Connty, Utah

#### Gentlemen:

Approval for Application for Permit to Drill the above referenced well is rescinded as of the above date in concert with action taken by Minerals Management Service.

If you intend to drill at this location at a future date, a new application for permit to drill may be submitted for State approval.

Sincerely,

Norm Stout

Administrative Assistant

NS/as